

AirMover™ 3 WindHandler™ 3



Portable Blower Machines

Three speed versatility and power reduces carpet drying times by up to 50%.



- **Your Choice of**

- » The economical standard AirMover 3 with molded handle, or
- » The WindHandler 3 with upright handle and transport wheels for added safety and convenience


- **Both models offer:**

- » 3 speeds of air movement for every type of job
- » A maximum air movement of 3,000 cfm for rapid drying of carpet and hard floors
- » Sturdy, four point motor mount to withstand heavy use and rough handling
- » Built-in carpet clip for flood restoration jobs





Technical Specifications


	AM3	WH3
Construction:	Rotationally molded polyethylene with molded offset handle and cord wrap	Same
Motor:	0.5 hp (373 watts), continuous duty, capacitor start, thermally protected, with four-point mount	Same
Fan Wheel:	9.6" dia. x 9.1" wide (24 cm dia. x 23 cm wide)	Same
Fan Speeds:	High – 1600 rpm Medium – 1350 rpm Low – 1050 rpm	Same Same Same
Airflow:	High – 3000 cfm (84 m ³ /min.) Medium – 2500 cfm (70 m ³ /min.) Low – 2000 cfm (56 m ³ /min.)	Same Same Same
Power Cable:	25 ft (7.6 m) 16/3 SJTW with three-wire molded plug	Same
Electrical:	120 volt AC, 60 Hz	Same
Dimensions (LxWxH):	20" x 16" x 18.8" (51 cm x 41 cm x 48 cm)	22.8" x 16" x 21.5" (58 cm x 41 cm x 55 cm)
Weight:	33.5 lbs (15 kg)	39 lbs (18 kg)
Approvals:	 UL Listed to U.S. and Canadian safety standards	Same

Specifications are subject to change without notice.

Performance Features



A selection of three air movement speeds provides maximum performance needed for each job.



Built-in carpet clip makes it easy to dry floors under carpets.



Airmover 3 offers three standing positions to allow air to be directed at different angles.

Windsor Innovations Protect:



Indoor Air Quality



Water



People



Environment